

IP55 Washguard Gearmotors - Right Angle - DC



90 Volt - TENV - Right-Angle

Output RPM	F.L. Torque (Lb.In.)	Input HP	Catalog Number	Stock	List Price	Model Number	Gearmotor Type & Frame	Ratio to 1	Arm. Volts DC	F.L. Amps DC	Overhung Load (lb.)	Dimensions (inches)					♥ Notes
												P	PB	X	XL	XH	
42	80	1/8	M1125275.00	✓	854	M31D25VZ3	13F60-31	60	90	2.2	235	3.13	3.8	4.5	10.86	6.36	S, US
250	25	1/8	M1125276.00	✓	854	M31D25VZ4	13F10-31	10	90	2.2	235	3.13	3.8	4.5	10.86	6.36	S, US
62	135	1/4	M1125277.00	✓	861	M32D25VZ6	13F40-32	40	90	3.7	235	3.25	3.8	4.5	12.86	8.36	S, US
125	90	1/4	M1125278.00	✓	861	M32D25VZ7	13F20-32	20	90	3.7	235	3.25	3.8	4.5	12.86	8.36	S, US
250	50	1/4	M1125279.00	✓	861	M32D25VZ8	13F10-32	10	90	3.7	235	3.25	3.8	4.5	12.86	8.36	S, US

Specifications are subject to change without notice

♥ Note listing on inside back flap

12 Volts - TENV - Right-Angle

Output RPM	F.L. Torque (Lb.In.)	Input HP	Catalog Number	Stock	List Price	Model Number	Gearmotor Type & Frame	Ratio to 1	Arm. Volts DC	F.L. Amps DC	Overhung Load (lb.)	Dimensions (inches)					♥ Notes
												P	PB	X	XL	XH	
62	135	1/4	M1125280.00	✓	818	M32D25VZ9	13F40-32	40	12	28	235	3.25	4.43	4.5	12.36	7.86	S, US
125	90	1/4	M1125281.00	✓	818	M32D25VZ10	13F20-32	20	12	28	235	3.25	4.43	4.5	12.36	7.86	S, US

Specifications are subject to change without notice

♥ Note listing on inside back flap

13 SERIES - DC

